

# NEW HOLLAND T4000 Deluxe & SuperSteer

T4020 | T4030 | T4040 | T4050



# SPECIFICATIONS

Models	T4020	T4030	T4040	T4050
<b>New Holland Engine*</b>	F5C	F5C	NEF	NEF
No. of cylinders / Capacity / Valves / Emissions Level	4 / 3200 / 2 / Tier III	4 / 3200 / 2 / Tier III	4 / 4500 / 2 / Tier III	4 / 4500 / 2 / Tier III
Aspiration	Turbocharged	Turbocharged	Turbocharged	Turbocharged
Intercooler	●	●	●	●
Approved Biodiesel Blend	B100**	B100**	B100**	B100**
Rated Engine Power ISO TR14396 - ECE R120 [kW/hp(CV)]	48/65	57/78	63/86	71/97
Rated Engine Speed (rpm)	2300	2300	2300	2300
Max. Torque ISO TR14396 at 1300rpm (Nm)	290	330	363	398
Torque reserve (%)	46	39	39	36
Optimum fuel consumption (g/kWh)	225	223	219	219
Fuel tank capacity (l)	75	75	90	90
Service Interval (hrs)	500	500	600	600
<b>Transmission</b>				
Electro Hydraulic Diff. Lock	●	●	●	●
<b>16 X 16 Shuttle Command™ (30kph/40kph)</b>	●	●	●	● (40kph only)
<b>28 X 16 Shuttle Command™ [Optional Creeper (30kph/40kph)]</b>	○	○	○	○ (40kph only)
<b>16 X 16 Powershuttle (30kph/40kph)</b>	○	○	○	○ (40kph only)
<b>32 X 16 Dual Command™ (30kph/40kph)</b>	○	○	○	○ (40kph only)
<b>44 X 16 Dual Command™ [Optional Creeper (30kph/40kph)]</b>	○	○	○	○ (40kph only)
<b>Front Axle</b>				
2WD Front Axles	○	○	○	-
4WD Front Axles	●	●	●	●
SuperSteer™ Front Axle	○	○	○	○
Steering angle Standard / SuperSteer Front Axle (°)	55 / 76	55 / 76	55 / 76	55 / 76
Turn radius 2WD / 4WD / SuperSteer Front Axle (mm)	3670 / 3890 / 3415	3670 / 3890 / 3415	3670 / 3890 / 3415	3670 / 3890 / 3415
<b>Hydraulic system</b>				
Standard pump flow / Optional MegaFlow™ pump flow (lpm)	48.6 / 63.8	48.6 / 63.8	48.6 / 63.8	48.6 / 63.8
Mechanical draft control (MDC)	●	●	●	●
Lift-O-Matic™	●	●	●	●
Electronic draft control (EDC)	○	○	○	○
Continuous Lift capacity through the range (610mm behind the ball bar ends) (kg)	2100	2100	2100	2100
Max Lift capacity at ball ends with arms horizontal (kg)	2900	2900	2900	2900
Max. no. rear remotes	6 (4+2)	6 (4+2)	6 (4+2)	6 (4+2)
Front Lift & PTO	○	○	○	○
<b>PTO</b>				
540	●	●	●	●
540 std 540/540E or 540/540E/1000 OPTION	○	○	○	○
<b>Operator environment</b>				
Suspended Platform (with ROPS)	○	○	○	○
Cab	●	●	●	●
Optional Air Conditioning	○	○	○	○
Blue Cab	○	○	○	○
Max. noise level*** dB(A)	78	78	78	78
<b>Dimensions &amp; Weights ****</b>				
Overall length (4WD) (mm)	3493	3493	3580	3580
Height to top of Rops (Up / Down) (mm)	2443 / 1930	2443 / 1930	2443 / 1930	2443 / 1930
Height to top of cab (mm)	2332	2332	2332	2332
ROPS Weights***** (2WD/4WD) (kg)	2620/2870	2620/2870	2700/2950	-/3000
Cab Weights***** (2WD/4WD) (kg)	2820/3070	2820/3070	2900/3150	-/3200
Max permissible weight (2WD/4WD) (kg)	4800/5250	4800/5250	4800/5250	4800/5250

\*Developed by CNH Engine Corporation \*\*Conditions Apply \*\*\*Cab Model Only \*\*\*\*Rear Tyres 16.9R30 \*\*\*\*\*With driver (85kg) and full fuel tank ● Standard ○ Optional - Not Available

New Holland prefers **AMBRA** lubricants



**Your success - Our speciality**

**NEW HOLLAND TOP SERVICE 00800 64 111 111**

### 24/7 Support and Information

The call is free from a land line. Check in advance with your Mobile Operator if you will be charged. Alternatively call 01 2421881.

Visit our web site for UK: [www.newholland.com/uk](http://www.newholland.com/uk) - for ROI: [www.newholland.com/ie](http://www.newholland.com/ie)

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in Italy - 02/08 - TP01 - (Turin)

AT YOUR OWN DEALER



**ASK FOR A TEST DRIVE!**



80007/INB